



ACIME FRAME - CONCEPTION AND PRODUCTION SITE 1, avenue de l'Europe - 62720 Rinxent - France +33 (0) 3 21 10 25 30 contact@acimeframe.com - www.acimeframe.com/EN/ Electric jacks inhibit the resonance of the lying surface.

Remote control for electrical movements, patient's access and autonomy.

Full Washable System<sup>®</sup> : Removable without any tools in record time. Velco-free mattress.

HYGIENE

Steering handles and brake pedals accessible from both ends. Backup battery (option).

HANDLING



PATIENT COMFORT

## SPECIFICATIONS

Overall width: 700 mm Overall length: 2050 mm

Adjustable height: 600 to 1000 mm Lying width: 620 / 720 mm Lying length: 1900 mm

Backrest: 0° to 72° Trendelenburg / anti-trend: -15°/+15°

Wheels: Ø200 mm with central braking

Mattress thickness: 80 mm

## Maximum load: 300 kg

## STANDARD FEATURES

Steel frame with epoxy coating 4 wheels + 5th directional wheel Central braking Mattress with PU cover Standard IV pole Protection bumpers 2 IV pole holders 2 foldable barriers Electric backrest, adjustable height and knee break with remote control Fixed handles on both ends sides Wheel control pedal at head and foot sides



Patient's lockable remote control



Adjustable backrest frame for a headrest installation

## OPTIONAL EXTRAS

(non-exhaustive list, please contact us)

2 foldable handles at the head end side
2 foldable handles at the foot end side
2 safety straps holders
Dining tray on barriers
Paper roll holder
Urine pouch holder
Child-friendly protection barriers
2 stainless universal rail for accessories
Non-standard colour for mattress cover
Ultra-confort mattress
EasyGliss mattress
Hand surgery table
Stomato headrest
Articulated IV pole fixed on the frame
Telescopic IV pole

Skot Chir